



Telecommunications
Standards Advisory
Committee (TSAC)

Technical Specification

Cellular Base Station
and Repeater System

**Draft IMDA TS CBS
Issue 1 Rev 2, August 2020**

Info-communications Media Development Authority
10 Pasir Panjang Road
#03-01 Mapletree Business City
Singapore 117438

© 2020 Info-communications Media Development Authority. All rights reserved.

This document may be downloaded from the IMDA website at <http://www.imda.gov.sg> and shall not be distributed without written permission from IMDA

Acknowledgement

The Info-communications Media Development Authority (IMDA) and the Telecommunications Standards Advisory Committee (TSAC) would like to acknowledge the following members of the TSAC Focus Area 6 and Task Force (TF) for Cellular Base Station and Repeater System / Cellular Mobile Terminal (TSAC CBS/CMT TF) for their invaluable contributions to the preparation of this Technical Specification:

Draft IMDA TS CBS Issue 1 Rev 2, Aug 2020	Technical Specification for Cellular Base Station and Repeater System
Focus Area 6 Chairperson	Dr Oh Ser Wah, CEO, Whizpace Pte Ltd
CBS/CMT Task Force Chairman(s)	Dr David Soldani; CSO Office Huawei (ASIA Pacific Region), CTO and CSO Huawei (Australia)
	Mr Kuan Wai Mun; Director, Radio Network Performance, Singapore Telecommunications Ltd
Editor	Dr Ma Yugang, Senior Scientist, Institute for Infocomm Research
Secretary	Dr Lim Wai Yean, Senior Manager, Infocomm Media Development Authority

List of TSAC FA 6 CBS/CMT TF Members (2018-2021)

S/N	Organisation	Name
1	Apple	Mr Song Qiaojian, APAC Regulatory Compliance Manager
2	Ericsson Telecommunications Pte Ltd	Mr Albert Tioe, Principal Solution Architect
3	Ericsson Telecommunications Pte Ltd	Mr Derek Wang, Principal Solution Architect
4	Huawei International Pte Ltd	Mr Scott Zhang, Vice President, Huawei International
5	M1 Limited	Mr Simon Foo, General Manager
6	Nokia Corporation	Mr Guillaume Mascot, Head of Government Relations APJ
7	Nanyang Technological University	A/P Teh Kah Chan
8	National University of Singapore	A/P Biplab Sikdar
9	Rohde & Schwarz	Mr Mahesh Basavaraju, Market Segment Manager - Wireless Communication
10	Singapore University of Technology and Design	A/P Yuen Chau
11	StarHub Ltd	Mr Steven Chia
12	TPG Telecom Pte Ltd	Mr Dennis Woo, Core Manager
13	TPG Telecom Pte Ltd	Mr Kenneth Loh, RF Manager

Telecommunications Standards Advisory Committee (TSAC)

The TSAC advises IMDA on the setting of ICT standards as well as on the development and recommendation of specifications, standards, information notes, guidelines and other forms of documentation for adoption and advancement of the standardisation effort of the Singapore ICT industry (hereafter termed “IMDA Standards”).

Telecommunications standards-setting in Singapore is achieved with the assistance of TSAC, where professional, trade and consumer interest in telecommunications standards is represented on the TSAC with representatives from network and service operators, equipment suppliers and manufacturers, academia and researchers, professional bodies and other government agencies.

List of TSAC Members (2018-2021)

TSAC Chairman:

Mr Raymond Lee Head (Regulatory Technology)
Infocomm Media Development Authority (IMDA)

TSAC Members:

Mr Yip Yew Seng	Honorary Secretary Association of Telecommunications Industry of Singapore (ATIS)
Dr Kang Cheng Guan	Senior Director, Security & Emergency Planning Energy Market Authority (EMA)
Mr Allan Koh	Senior Development Partner, Electronics & IT Enterprise Singapore (ESG)
Mr Hong Tse Min	Senior Assistant Director, Infocomm Resource & Technology Infocomm Media Development Authority (IMDA)
Dr Sun Sumei	Department Head, Communications & Networks Institute for Infocomm Research (I2R)
Mr Peter Quek	Group Director - IT, Cybersecurity & Digital Services Land Transport Authority (LTA)
Mr Denis Seek	CTO M1 Limited
Mr Anil Nihalani	Head, Digital Products & Technology Mediacorp Pte Ltd
Prof Teh Kah Chan	Associate Professor, School of EEE Nanyang Technological University (NTU)
Mr Biplab Sikdar	Associate Professor, Department of ECE National University of Singapore (NUS)
Dr Peter Loh Kok Keong	Associate Professor and Deputy Programme Director, Infocomm Technology Cluster Singapore Institute of Technology (SIT)
Mr Edmund Quek Han Yeow	Director, Radio Network Quality Singapore Telecommunications Ltd (Singtel)
Ms Sarah Tay	VP, Mobile & Fixed Voice Networks StarHub Ltd
Mr Kenneth Loh	RF Manager TPG Telecom

This page is intentionally left blank.

Content

Section (§)	Title	Page
1.	Scope	2
2.	References	2
3.	Abbreviations	4
4.	General Requirements	5
	4.1 Power Supply	5
	4.2 Electromagnetic Compatibility (EMC) and Equipment Safety Requirements	5
5.	Technical Requirements	7
	5.1 Operating Frequencies	7
	5.2 Radio Interface Requirements	7
Annex A	CBS Conformance Testing / Verification Checklist	9
Annex B	Corrigendum / Addendum	13
	Changes to IMDA TS CBS Issue 1, 1 Jul 17	
	Changes to IMDA TS CBS Issue 1, Oct 16	
	Changes to IDA TS CBS Issue 1, Jun 11	
	Changes to IDA TS GSM-BS Issue 1 Rev 2 and 3G-BS Issue 1 Rev 1, May 11	

NOTICE

THE INFO-COMMUNICATIONS MEDIA DEVELOPMENT AUTHORITY (“IMDA”) MAKES NO REPRESENTATION OR WARRANTY OF ANY KIND WITH REGARD TO THE MATERIAL PROVIDED HEREIN AND EXCLUDES ANY EXPRESS OR IMPLIED WARRANTIES OR CONDITIONS OF NON-INFRINGEMENT, MERCHANTABILITY, SATISFACTORY QUALITY AND FITNESS FOR A PARTICULAR PURPOSE. SUBJECT TO THE MAXIMUM EXTENT PERMITTED UNDER LAW, IMDA SHALL NOT BE RESPONSIBLE OR LIABLE TO YOU OR ANY THIRD PARTY FOR ANY ERRORS AND/OR OMISSIONS CONTAINED HEREIN OR FOR ANY LOSSES OR DAMAGES (INCLUDING ANY LOSS OF PROFITS, BUSINESS, GOODWILL OR REPUTATION, AND/OR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES) IN CONNECTION WITH THE USE OF THIS MATERIAL.

IMDA RESERVES THE RIGHT TO CHANGE, MODIFY OR ADD TO ANY PART OF THIS DOCUMENT. NOTHING HEREIN IS INTENDED TO CREATE OR IMPOSE ANY BINDING LEGAL OBLIGATIONS OR LIABILITY WHATSOEVER ON IMDA, WHETHER EXPRESSED OR IMPLIED, AND WHETHER CONTRACTUAL OR OTHERWISE. WITHOUT PREJUDICE TO THE FOREGOING, NOTHING IN THIS DOCUMENT SHALL BIND IMDA TO ADOPT ANY PARTICULAR COURSE OF ACTION. CONSEQUENTLY, NOTHING HEREIN SHALL BE CONSTRUED AS GRANTING ANY EXPECTATION, WHETHER PROCEDURAL OR SUBSTANTIVE IN NATURE, THAT IMDA WILL TAKE OR NOT TAKE ANY PARTICULAR COURSE OF ACTION IN THE FUTURE, ARISING FROM OR DUE TO ANYTHING IN THIS DOCUMENT OR IN THE EXERCISE OF ITS DISCRETION AS A PUBLIC AUTHORITY.

IMDA DRAWS ATTENTION TO THE POSSIBILITY THAT ANY PRACTICE OR IMPLEMENTATION OF THIS STANDARD/SPECIFICATION MAY INVOLVE THE USE OF INTELLECTUAL PROPERTY RIGHTS AND TAKES NO POSITION CONCERNING THE EXISTENCE, VALIDITY AND/OR APPLICABILITY OF ANY SUCH INTELLECTUAL PROPERTY RIGHTS, WHETHER ASSERTED BY TSAC MEMBERS OR ANY THIRD PARTY.

AS OF THE DATE OF ISSUANCE OF THIS STANDARD/SPECIFICATION, IMDA HAS NOT RECEIVED WRITTEN NOTICE OF ANY PATENT RIGHTS WHICH MAY BE RELEVANT IN RELATION TO THE IMPLEMENTATION OF THIS STANDARD/SPECIFICATION. HOWEVER, IMPLEMENTERS ARE CAUTIONED THAT THIS MAY NOT REPRESENT THE LATEST INFORMATION AND ARE THEREFORE STRONGLY URGED TO CHECK WITH THE RELEVANT DATABASE IN ITU, ISO, IEC OR THE RELEVANT STANDARDS DEVELOPMENT ORGANISATION FOR INFORMATION OF INTELLECTUAL PROPERTY RIGHTS. IMPLEMENTERS ARE ADVISED TO OBTAIN THEIR OWN PROFESSIONAL, TECHNICAL AND/OR LEGAL ADVICE AND CONDUCT ALL NECESSARY DUE DILIGENCE, INCLUDING BUT NOT LIMITED TO MAKING SUCH INVESTIGATIONS OR SEEKING CLARIFICATIONS AS MAY BE APPROPRIATE, IN REGARD TO ANY DECISION OR ACTION THAT THEY INTEND TO TAKE, OR PRIOR TO THE IMPLEMENTATION OF ANY STANDARD/SPECIFICATION AS MAY BE REQUIRED.

Technical Specification for Cellular Base Station and Repeater System

1 Scope

This Specification defines the minimum technical requirements for Cellular Base Station and Repeater System (broadly termed “CBS” in this Specification) to be used in the Public Mobile Radio Communication System and services which employ:

- (a) ITU IMT-2000 radio interface technologies (UTRA FDD and E-UTRA FDD) identified in ITU-R M.1457-14, and transposed from 3GPP Release 8 and 9;
- (b) ITU IMT-Advanced radio interface technologies (LTE-Advanced) identified in ITU-R M.2012-4, and transposed from 3GPP Release 10 and beyond;
- (c) LTE-Advanced technology series from 3GPP Release 13 onwards, marked with LTE-Advanced Pro; and
- (d) ITU IMT-2020 radio interface technologies (5G NR) identified in ITU-R M.2412-0, and transposed from 3GPP Release 15 and beyond.

Note: CBS’ support of the Global System for Mobile Communications (GSM¹) technology is no longer required after 31 March 2017.

2 References

For the technical requirements captured in this Specification, reference has been made to the following standards. Where versions are not indicated, implementation of this Specification shall be based on current and valid versions of these standards published by the respective Standards Development Organisations².

- [1] ETSI EN 301 908-1: IMT cellular networks; Harmonised Standard for access to radio spectrum; Part 1: Introduction and common requirements
- [2] ETSI EN 301 908-3: IMT cellular networks; Harmonised Standard for access to radio spectrum; Part 3: CDMA Direct Spread (UTRA FDD) Base Stations (BS)
- [3] ETSI EN 301 908-11: IMT cellular networks; Harmonised Standard covering essential requirements of Directive 2014/53/EU; Part 11: CDMA Direct Spread (UTRA FDD) Repeaters
- [4] ETSI EN 301 908-14: IMT cellular networks; Harmonised Standard for access to radio spectrum; Part 14: Evolved Universal Terrestrial Radio Access (E-UTRA) Base Stations (BS)
- [5] ETSI EN 301 908-15: IMT cellular networks; Harmonised Standard for access to radio spectrum; Part 15: Evolved Universal Terrestrial Radio Access (E-UTRA) FDD Repeaters
- [6] Draft ETSI EN 301 908-18: IMT cellular networks; Harmonised Standard for access to radio spectrum; Part 18: E-UTRA, UTRA and GSM/EDGE Multi-Standard Radio (MSR) Base Station (BS) 3GPP Rel-15 update including NR
- [7] ETSI EN 301 489-1: EMC standard for radio equipment and services; Part 1: Common technical requirements
- [8] ETSI EN 301 489-50: EMC standard for radio equipment and services; Part 50: Specific conditions for Cellular Communication Base Station (BS), repeater and ancillary equipment

¹ Use of the GSM RIT for base stations and repeaters in the GSM900 and GSM1800 bands according to the ETSI EN 301 502 and EN 300 609-4 has ceased after 31 March 2017.

² Implementers of these ETSI standards should check with the ETSI Web Server (<http://ipr.etsi.org>) whether Intellectual Property Rights have been declared to ETSI.

- [9] ITU-R M.1457-14: Detailed specifications of the terrestrial radio interfaces of International Mobile Telecommunications-2000 (IMT-2000)
- [10] ITU-R M.2012-4: Detailed specifications of the terrestrial radio interfaces of International Mobile Telecommunications-Advanced (IMT-Advanced)
- [11] IEC CISPR 32: Electromagnetic compatibility of multimedia equipment – Emission requirements
- [12] IEC CISPR 35: Electromagnetic compatibility of multimedia equipment – Immunity requirements
- [13] IEC 60950-1: Information technology equipment – Safety – Part 1: General requirements
- [14] IEC 62368-1: Audio/video, information and communication technology equipment – Part 1: Safety requirements
- [15] Recommendation ITU-R M.[IMT-2020.SPECS] - Detailed specifications of the terrestrial radio interfaces of International Mobile Telecommunications-2020 (IMT-2020)
- [16] Draft ETSI EN 301 908-24: IMT cellular networks; Harmonised Standard for access to radio spectrum; Part 24: New Radio (NR) Base Stations (BS)
- [17] IMDA Technical Specification for Short Range Devices
- [18] FCC Part15 §15.407
- [19] ANSI C63.10-2013: Procedures for compliance testing of unlicensed wireless devices

3 Abbreviations³

3GPP	3rd Generation Partnership Project
AC	Alternating Current
BS	Base Station
CBS	Cellular Base Station or Repeater
CDMA	Code Division Multiple Access
CISPR	International Special Committee on Radio Interference of the IEC
DC	Direct Current
EMC	Electromagnetic Compatibility
EMI	Electromagnetic Interference
EMS	Electromagnetic Sustainability
EN	European Standard
ETSI	European Telecommunications Standards Institute
E-UTRA	Evolved Universal Terrestrial Radio Access (also known as LTE)
FDD	Frequency Division Duplex
GSM	Global System for Mobile communications
ICNIRP	International Commission on Non-ionizing Radiation Protection
IEC	International Electrotechnical Commission
IMT	International Mobile Telecommunications
ITU	International Telecommunication Union
ITU-R	ITU Radiocommunication Sector
ITU-T	ITU Telecommunication Standardization Sector
LTE	Long Term Evolution (also known as E-UTRA)
MSR	Multi Standard Radio
NR	New Radio
OTA	Over The Air
RAT	Radio Access Technology
RF	Radio Frequency
RIT	Radio Interface Technology
SDO	Standards Development Organisation
SELV	Safety Extra-Low Voltage
TDD	Time Division Duplex
UTRA	Universal Terrestrial Radio Access (UTRA FDD also known as WCDMA)
WCDMA	Wideband Code Division Multiple Access

³ 3GPP™ and LTE™ are Trade Marks registered by ETSI for the benefit of its Members and 3GPP Organizational Partners.

4 General Requirements

4.1 Power Supply

The CBS may be AC powered or DC powered. For an AC powered equipment, the Specification shall be complied with when operating from an AC mains supply of voltage, $230V \pm 10\%$ and frequency, $50 \text{ Hz} \pm 2\%$. Where external power supply is used (e.g. AC/DC power converter), it shall not affect the capability of the equipment to meet the requirements of this Specification.

4.2 Electromagnetic Compatibility (EMC) and Equipment Safety Requirements

4.2.1 EMC assessment

For EMC assessment, the CBS shall be classified as equipment for fixed use. This equipment classification is used to determine the applicability of the EMC (emission and immunity) testing requirements based on §7 of ETSI EN 301 489-1 [7]. The ETSI EN 301 489-1 [7] standard shall be used in conjunction with the ETSI EN 301 489-50 [8] standard for CBS that may be capable of supporting two or more radio transmitters of different technologies, operating simultaneously; or processing two or more carriers in a RF bandwidth, with at least one carrier of a different radio access technology.

4.2.1.1 EMI or emission measurements

The following emissions measurements shall be performed on the CBS, where applicable:

- (a) Radiated emissions from associated ancillary equipment not incorporated in the CBS shall be measured to Class B requirements defined in §5 and Tables A.4 and A.5 of CISPR 32 [11]; or §8.2 of EN 301 489-1 [7];
- (b) Conducted emission at the DC power port of the CBS shall be measured according to §8.3 [7] of EN 301 489-1 [7];
- (c) Conducted emission at the AC mains port shall be measured for CBS with dedicated AC/DC power converter to Class B requirements defined in §5 and Table A.10 of CISPR 32 [11]; or §8.4 [7]. Equipment with DC power port which is powered by a dedicated AC/DC power converter is defined as AC mains powered equipment (§3.1.1 [9]); and
- (d) Conducted emission at the wired network port of the CBS shall be measured to Class B requirements defined in Table A.12 of CISPR 32 [11]; or §8.7 of EN 301 489-1 [7].

4.2.1.2 EMS or immunity testing

The following immunity tests may be performed on the CBS to requirements defined in CISPR 35 [12], or §9 of EN 301 489-1 [7], where applicable:

- (a) RF electromagnetic field (80 MHz to 6 GHz) at the enclosure of equipment;
- (b) Electrostatic discharge at the enclosure of equipment;
- (c) Fast transients (common mode) at DC power and AC main power ports that have cables longer than 3 m;
- (d) RF common mode 0.15 MHz to 80 MHz at DC power and AC mains power ports that have cables longer than 3 m;
- (e) Voltage dips and interruptions at AC mains power port of equipment with dedicated AC/DC power converter; and
- (f) Surges, common and differential mode at AC mains power port of equipment with dedicated

AC/DC power converter.

4.2.2 Equipment safety testing

4.2.2.1 Equipment safety testing or assessment shall be performed to requirements defined in IEC 60950-1 [13] or IEC 62368-1 [14], based on the following assumptions:

- (a) CBS is powered by a dedicated external power supply or AC/DC power converter; or
- (b) CBS is powered by AC power supply;
- (c) CBS operates with SELV in environments where overvoltage from telecommunication networks may be possible. SELV refers to voltages not exceeding 42.4 V peak or 60 V DC.

4.2.2.2 For CBS safety assessment performed with the hazard-based approach, the processes defined in IEC 62368-1 [14] shall be used:

- (a) Identify energy sources in the CBS;
- (b) Classify energy sources (effect on the body or combustible material, e.g. possibility of injury or ignition);
- (c) Identify safeguards for protection against energy sources; and
- (d) Consider the effectiveness of safeguards with respect to compliance criteria or requirements defined in the standard [14].

5 Technical Requirements

5.1 Operating Frequencies

5.1.1 The CBS shall operate within the frequency bands given in Table 1. Conformance with technical requirements outlined in this Specification is based on the assumption that the operating frequency bands are shared between systems of the IMT family. When LAA is supported, in addition to frequency bands in Table 1, the license-exempt spectrum given in Table 1a should be utilised.

Table 1: CBS Operating Frequency Bands

UTRA FDD Band	E-UTRAN Band	NR Band	Direction of Transmission	Frequency Range
I	1	n1	Transmit	2110 MHz – 2170 MHz
			Receive	1920 MHz – 1980 MHz
III	3	n3	Transmit	1805 MHz – 1880 MHz
			Receive	1710 MHz – 1785 MHz
VII	7	n7	Transmit	2620 MHz – 2690 MHz
			Receive	2500 MHz – 2570 MHz
VIII	8	n8	Transmit	925 MHz – 960 MHz
			Receive	880 MHz – 915 MHz
-	38	n38	Transmit and Receive	2570 MHz – 2620 MHz
-	40	n40	Transmit and Receive	2300 MHz – 2400 MHz
-	-	n77	Transmit and Receive	3300 MHz – 4200 MHz
-	-	n78	Transmit and Receive	3300 MHz – 3800 MHz
-	-	n257	Transmit and Receive	26500 MHz – 29500
-	-	n258	Transmit and Receive	24250 MHz – 27500 MHz
-	-	n261	Transmit and Receive	27500 MHz – 28350 MHz

Table 1a: License-exempt Bands for LAA

E-UTRA Operating Band ^{Note 1}	BS Transmit and Receive Frequency Range
46a	5150 MHz – 5250 MHz
46b	5250 MHz – 5350 MHz
46c	5470 MHz – 5725 MHz
46d	5725 MHz – 5925 MHz ^{Note 2}
Note 1: Band 46 is divided into four sub-bands Note 2: LAA operating in band 46d shall only transmit and receive within Singapore's frequency spectrum allocation (5725 MHz – 5850 MHz)	

5.1.2 The precise operating frequency range of a CBS shall follow that of the Network Operator from whom the service is provided.

5.2 Radio Interface Requirements

5.2.1 Manufacturers or suppliers shall demonstrate that the CBS (base stations or repeaters) have been tested and certified for operating in the frequency bands stated in Table 1 clause 5.1.1, and conformity to any or a combination of standards given in Table 2 for Base Stations or Table 3 for Repeaters. The CBS shall comply with the applicable requirements specified in these standards, in addition to the requirements identified in

the ETSI EN 301 908-1 [1] for compliance by the base stations and repeaters.

Table 2: IMT RITs in EN 301 908-1 [1] and the Standards Parts for Base Stations

IMT-2000 / IMT-Advanced / IMT-2020 terrestrial RIT		RAT name in SDO	Reference SDO	EN 301 908 Part
(a)	IMT-2000 CDMA Direct Spread	UTRA FDD	ETSI (3GPP)	Part 3 [2]
(b)	LTE-Advanced	E-UTRA	ETSI (3GPP)	Part 14 [4]
(c)	IMT-2000 CDMA Direct Spread, LTE-Advanced and IMT-2020	E-UTRA, UTRA and NR	ETSI (3GPP)	Part 18 [6] covers MSR capable CBS.
(d), (e)	IMT-2020	NR	ETSI (3GPP)	Part 24 [16]

Table 3: IMT RITs in EN 301 908-1 [1] and the Standards Parts for Repeaters

IMT-2000 / IMT-Advanced terrestrial RIT		RAT name in SDO	Reference SDO	EN 301 908 Part
(a)	IMT-2000 CDMA Direct Spread	UTRA FDD	ETSI (3GPP)	Part 11 [3]
(b)	LTE-Advanced	E-UTRA FDD	ETSI (3GPP)	Part 15 [5]

- 5.2.2. The effective isotropic radiating power (EIRP) of any base stations or repeaters in operation shall be limited to 62dBm/5MHz. Use of the CBS shall comply with the International Commission on Non-Ionizing Radiation Protection (ICNIRP) guidelines for limiting exposure to time-varying electric, magnetic, and electromagnetic fields (up to 300 GHz).
- 5.2.3. CBS that supports E-UTRA with LAA shall be tested for compliance with the applicable requirements following test methods and conditions given in EN 301 908-14 [4], or FCC Part15 [18] and ANSI C63.10-2013 [19]. Power output limits and spurious emissions shall be tested and certified for conformity to the relevant requirements as given IMDA TS SRD [17].

Annex A

CBS Conformance Testing / Verification Checklist

This Checklist is intended for facilitating Supplier's Declaration of Conformity to the requirements defined in the IMDA Technical Specification for Cellular Base Stations and Repeater Equipment ("IMDA TS CBS").

Please note:

"**CR**" indicates that the general or technical requirement set out in a particular section or sub-section ("§") of the IMDA TS CBS is a **Compliance Requirement**.

"**M**" means that it shall be **Mandatory** for the CBS to comply with the requirement set out in the IMDA TS CBS § cited in this Checklist (Table given below).

"**C**" means that compliance with the technical requirement set out in the IMDA TS CBS § cited in this Checklist is **Conditional**. In this case, the need to comply is contingent on the type of CBS (base station or repeater), RIT/RAT and application indicated in the remarks column.

"**V**" means that compliance with the requirement is **Voluntary**.

"**NA**" means that the requirement is **Not Applicable**.

IMDA TS CBS §	Parameter	Reference [n] given in § 2 of IMDA TS CBS	CR	Yes /No/ NA	Remarks
1	IMT-2000 / IMT-Advanced /LTE-Advanced / LTE-Advanced Pro / IMT-2020 RITs	ITU-R M.1457-14 [9], M.2012-4 [10]	M		Refer to §5.2 of IMDA TS CBS
4.1	Power supply	§3.1.1 [11]	M		CBS powered by a dedicated AC/DC power converter is defined as AC mains powered equipment.
4.2	EMC and safety requirements	Heading	-	-	
4.2.1	EMC assessment	§7 [7]	M		[7] shall be used in conjunction with [8] for CBS capable of supporting two or more RATs; or processing two or more carriers in a RF bandwidth, with at least one carrier of a different RAT
4.2.1.1 (a)	Radiated emission	Tables A.4 and A.5 [11]; or §8.2 [7]	C		Applicable to ancillary equipment not incorporated in the CBS
4.2.1.1 (b)	Conducted emission: DC power port	§8.3 [7]	C		
4.2.1.1 (c)	Conducted emission: AC mains power port	Table A.10 [11]; or §8.4 [7]	C		Applicable to CBS with dedicated AC/DC power converter
4.2.1.2 (a)	RF electromagnetic field (80 MHz to 6 GHz)	§4.2.2.2 [12]; or §9.2 [7]	V		
4.2.1.2 (b)	Electrostatic discharge	§4.2.1 [12]; or §9.3 [7]	V		
4.2.1.2 (c)	Fast transients common mode	§4.2.4 [12]; or §9.4 [7]	V		Applicable to CBS with dedicated AC/DC power converter; DC power port with cable longer than 3 m
4.2.1.2 (d)	RF common mode 0.15 MHz to 80 MHz	§4.2.2.3 [12]; or §9.5 [7]	V		
4.2.1.2 (e)	Voltage dips and interruptions	§4.2.6 [12]; or §9.7 [7]	V		Applicable to CBS with dedicated AC/DC power converter; wired network ports
4.2.1.2 (f)	Surges	§4.2.5 [12]; or §9.8 [7]	V		
4.2.2	Equipment safety testing	IEC 60950-1 [13]; or IEC 62368-1 [14]	M		

Annex A

CBS Conformance Testing / Verification Checklist (Cont'd)

IMDA TS CBS §	Parameter	Reference [n] given in § 2 of IMDA TS CBS	CR	Yes /No/ NA	Remarks
5.1	Operating frequencies		M		
5.2	Radio interface requirements	Table C-1 [1], [9], [10] and [15], where applicable	M		State the RITs and the 3GPP Releases supported by the CBS, e.g. 3GPP Release 8, 9, 10 and beyond.
	Radiated emissions	§4.2.2 [1]	M		Applicable to base stations and repeaters
5.2 - Table 2 (a)	Spectrum emissions mask	§4.2.2 [2]	C		Base stations that support the UTRA FDD technology, shall be tested to comply with these essential requirements as defined in [2].
	Adjacent channel leakage power ratio (ACLR)	§4.2.3 [2] See Note 1	C		
	Transmitter spurious emissions	§4.2.4 [2]	C		
	Base station maximum output power	§4.2.5 [2]	C		
	Transmitter intermodulation	§4.2.6 [2]	C		
	Receiver spurious emissions	§4.2.7 [2]	C		
	Blocking characteristics	§4.2.8 [2]	C		
	Receiver intermodulation characteristics	§4.2.9 [2]	C		
	Receiver adjacent channel selectivity (ACS)	§4.2.10 [2]	C		
	Home BS output power for adjacent channel protection	§4.2.11 [2]	C		
Reference sensitivity level	§4.2.12 [2] See Note 2	C			
<p>Note 1: For MSR capable BS (defined in [6]), conformance with the UTRA ACLR requirement is demonstrated through the requirement in §4.2.3 [2].</p> <p>Note 2: For MSR capable BS (defined in [6]), conformance with the reference sensitivity level requirement is demonstrated through the requirement in §4.2.12 [2].</p>					
5.2 - Table 2 (b)	Operating band unwanted emissions	§4.2.2 [4]	C		Base stations that support the E-UTRA technology, shall be tested to comply with these essential requirements as defined in [4].
	Adjacent channel leakage power ratio (ACLR)	§4.2.3 [4] See Note 3	C		
	Transmitter spurious emissions	§4.2.4 [4]	C		
	Base station maximum output power	§4.2.5 [4]	C		
	Transmitter intermodulation	§4.2.6 [4]	C		
	Receiver spurious emissions	§4.2.7 [4]	C		
	Blocking characteristics	§4.2.8 [4]	C		
	Receiver intermodulation characteristics	§4.2.9 [4]	C		
	Adjacent channel selectivity (ACS) and narrowband blocking	§4.2.10 [4]	C		
	Home BS output power for adjacent UTRA channel protection	§4.2.11 [4]	C		
	Home BS output power for adjacent E-UTRA channel protection	§4.2.12 [4]	C		
Home BS output power for co-channel E-UTRA protection	§4.2.13 [4]	C			
Reference sensitivity level	§4.2.14 [4] See Note 4	C			
<p>Note 3: For MSR capable BS (defined in [6]), conformance with the E-UTRA ACLR requirement is demonstrated through the requirement in §4.2.3 [4].</p> <p>Note 4: For MSR capable BS (defined in [6]), conformance with the reference sensitivity level requirement is demonstrated through the requirement in §4.2.14 [4].</p>					

Annex A

CBS Conformance Testing / Verification Checklist (Cont'd)

IMDA TS CBS §	Parameter	Reference [n] given in § 2 of IMDA TS CBS	CR	Yes /No/ NA	Remarks
5.2 - Table 2 (c)	Operating band unwanted emissions	§4.2.2 [6]	C		MSR capable Base stations that support the E-UTRA, UTRA and/or NR technologies, shall be tested to comply with these essential requirements as defined in [6].
	Adjacent channel leakage power ratio (ACLR)	§4.2.3 [6]	C		
	Transmitter spurious emissions	§4.2.4 [6]	C		
	Base station maximum output power	§4.2.5 [6]	C		
	Transmitter intermodulation	§4.2.6 [6]	C		
	Receiver spurious emissions	§4.2.7 [6]	C		
	In-band blocking	§4.2.8 [6]	C		
	Out-of-band blocking	§4.2.9 [6]	C		
	Receiver intermodulation characteristics	§4.2.10 [6]	C		
	Narrowband blocking	§4.2.11 [6]	C		
Reference sensitivity level	§4.2.12 [6]	C			
5.2 - Table 2 (d)	Operating band unwanted emissions	§4.3.2 [16]	C		Conducted requirements for Base stations that support the NR technology, shall be tested to comply with these essential requirements as defined in [16].
	Adjacent channel leakage power ratio (ACLR)	§4.3.3 [16] See note 5	C		
	Transmitter spurious emissions	§4.3.4 [16]	C		
	Base station maximum output power	§4.3.5 [16]	C		
	Transmitter intermodulation	§4.3.6 [16]	C		
	Receiver spurious emissions	§4.3.7 [16]	C		
	In-band blocking	§4.3.8 [16]	C		
	Out-of-band blocking	§4.3.9 [16]	C		
	Receiver intermodulation characteristics	§4.3.10 [16]	C		
	Narrowband blocking	§4.3.11 [16]	C		
Reference sensitivity level	§4.3.12 [16] See note 6	C			
Note 5: For MSR capable BS (defined in [6]), conformance with the NR ACLR requirement is demonstrated through the requirement in §4.3.3 [16].					
Note 6: For MSR capable BS (defined in [6]), conformance with the NR reference sensitivity level requirement is demonstrated through the requirement in §4.3.12 [16].					
5.2 – Table 2 (e)	OTA Operating band unwanted emissions	§4.3.13 [16]	C		OTA Base stations that support the NR technology, shall be tested to comply with these essential requirements as defined in [16].
	OTA Adjacent channel leakage power ratio (ACLR)	§4.3.14 [16]	C		
	OTA Transmitter spurious emissions	§4.3.15 [16]	C		
	Radiated transmit power	§4.3.16 [16]	C		
	OTA Base station maximum output power	§4.3.17 [16]	C		
	OTA Transmitter intermodulation	§4.3.18 [16]	C		
	OTA Receiver spurious emissions	§4.3.19 [16]	C		
	OTA In-band Blocking and narrow band blocking characteristics	§4.3.20 [16]	C		
	OTA Out-of-band blocking characteristics	§4.3.21 [16]	C		
	OTA Receiver intermodulation characteristics	§4.3.22 [16]	C		
	OTA Adjacent channel selectivity (ACS)	§4.3.23 [16]	C		
	OTA sensitivity	§4.3.24 [16]	C		
	OTA Reference sensitivity	§4.3.25 [16]	C		
5.2 - Table 3	Operating band unwanted emissions	§4.2.2 [3]	C		Repeaters that support the UTRA FDD
	Spurious emissions	§4.2.3 [3]	C		

(a)	Maximum output power	§4.2.4 and Annex A [3]	C		technology, shall be tested to comply with these essential requirements as defined in Chapter 5 [3].
	Input intermodulation	§4.2.5 and Annex A [3]	C		
	Out-of-band gain	§4.2.6 and Annex A [3]	C		
	Adjacent channel rejection ratio	§4.2.7 and Annex A [3]	C		
	Output intermodulation	§4.2.8 and Annex A [3]	C		
5.2 - Table 3 (b)	Operating band unwanted emissions	§4.2.2 and Annex A [5]	C		Repeaters that support the E-UTRA FDD technology, shall be tested to comply with these essential requirements as defined in Chapter 5 [5].
	Spurious emissions	§4.2.3 and Annex A [5]	C		
	Maximum output power	§4.2.4 and Annex A [5]	C		
	Input intermodulation	§4.2.5 and Annex A [5]	C		
	Out-of-band gain	§4.2.6 and Annex A [5]	C		
	Adjacent channel rejection ratio	§4.2.7 and Annex A [5]	C		
	Output intermodulation	§4.2.8 and Annex A [5]	C		

Annex A

Additional Conformance Testing / Verification Checklist for LAA-enabled CBS (Cont'd)

IMDA TS CBS §	Parameter	Reference [n] given in § 2 of IMDA TS CBS	CR	Yes/No/NA	Remarks
5.1	Operating frequencies		M		Precise operating frequency range of an E-UTRA CBS with LAA shall follow that of the network operator from whom service is provided.
5.2.1	Maximum RF power	Table 1 [17]	M		
	Spurious emission limits	Table 1-a [17]	M		
	DFS functions	[17] or §4.2.16 [4]	M		
	Energy detection threshold	§4.2.15 [4]	M		
	Maximum channel occupancy time	§4.2.15 [4]	M		
	Conformance tests at band 46	§5.3.14 [4], or [18] and [19]	M		

Annex B

Corrigendum / Addendum

Revised TS		Items Changed	Date of Issue
Page	Reference		
Changes to IMDA TS CBS Issue 1 Rev 1, Jul 17			
5 5 5 and 6 7 8 8 8 and 12 9	§4.3.1.2 §4.3 Table 1, Table 1a Table 2 §5.2.2 §5.2.3 and Annex A Annex A	<p>The IMDA TS CBS Issue 1 Rev 1 has been replaced by the IMDA TS CBS Issue 1 Rev 2.</p> <p>Changes were made to include specifications for 5G NR and to keep up with new developments that have taken place in the IMT systems of the network operators and standards.</p> <p>Main changes include:</p> <ul style="list-style-type: none"> (a) Removal of section on radiation safety (b) Replacing CISPR 24 with CISPR 35 for immunity testing (c) Removal of need to comply with ITU-T K.116 and IEC 60215 (d) Updating of CBS operating bands to include 5G NR; include license-exempt bands for LAA (e) Support for 5G NR (f) Included maximum power limits of equipment in operation (g) Included support for LAA-enabled CBS (h) Revision of Checklist to include support for 5G NR and to reflect changes in new developments in standards 	Aug 20

Revised TS		Items Changed	Date of Issue
Page	Reference		
Changes to IMDA TS CBS Issue 1, Oct 16			
2 and 7 7 9	§1 and §5.2 Table 2 §5.1.1 Table 1 Annex A	<p>The IMDA TS CBS Issue 1 has been replaced by the IMDA TS CBS Issue 1 Rev 1.</p> <p>Changes are intended to provide clarity of requirements for conformity assessment by equipment suppliers, in line with development that has taken place in the IMT systems of the network operators.</p> <p>Main changes include:</p> <ul style="list-style-type: none"> (e) Support for LTE-Advanced TDD RIT (E-UTRAN RAT); (f) Use of E-UTRAN band 38 (2570 MHz – 2615 MHz) and band 40 (2300 MHz – 2340 MHz) (g) Revision of Checklist for clarity in supporting LTE-Advanced TDD RIT (E-UTRAN RAT) 	1 Jul 17

Revised TS		Items Changed	Date of Issue
Page	Reference		
Changes to IDA TS CBS Issue 1, Jun 11			
2	§1	<p>The IDA TS CBS Issue 1 has been replaced by the IMDA TS CBS Issue 1.</p> <p>Changes are largely editorial to provide clarity of requirements for conformity assessment by equipment suppliers, in line with standards development that has taken place in the SDOs and the IMT systems adopted by network operators.</p> <p>Main changes include:</p> <ul style="list-style-type: none"> (h) Cessation of support for the GSM RITs by 1 April 2017; 	1 Oct 16

5	§4.3	(i) Updating of EMC and safety requirements for CBS;	
7	§5.2	(j) Updating of essential requirements for the support of IMT-Advanced / LTE-Advanced RITs; and	
8	Annex A	(k) Addition of a Checklist for facilitating suppliers' declaration of conformity to requirements defined in the Specification.	

Revised TS		Items Changed	Effective Date
Page	Reference		
Changes to IDA TS GSM-BS Issue 1 Rev 2 and 3G-BS Issue 1 Rev 1, May 11			
		<p>Title of Specification has been renamed as "Technical Specification for Cellular Base Station and Repeater System" (IDA TS CBS Issue 1).</p> <p>The Technical Specification has superseded the following two IDA Technical Specifications:</p> <p>(a) IDA TS GSM-BS Issue 1 Rev 2 (b) IDA TS 3G-BS Issue 1 Rev 1</p> <p>Changes are mainly editorial in nature, in which the essential technical requirements for compliance formerly defined under the two Specifications (TS GSM-BS and 3G-BS) are now incorporated as one.</p>	Jun 11
3 4	§1.1 §2.2.1	It also includes the requirements for the Radio Access Technology, E-UTRA.	