



Telecommunications  
Standards Advisory  
Committee (TSAC)

---

Technical Specification

---

Television  
White Space Devices

---

**Draft IDA TS WSD  
Issue 1, March 2015**

Infocomm Development Authority of Singapore  
Resource Management & Standards  
10 Pasir Panjang Road  
#10-01 Mapletree Business City  
Singapore 117438

© Copyright of IDA, 2015

This document may be downloaded from the IDA website at <http://www.ida.gov.sg> and shall not be distributed without written permission from IDA.

## Acknowledgement

The Info-communications Development Authority of Singapore (IDA) and the Telecommunications Standards Advisory Committee (TSAC) would like to acknowledge the following members of the TSAC Working Group 6, Task Force 1 (TSAC WG6 TF1) for their invaluable contributions to the preparation of this Technical Specification:

<b>IDA TS WSD Issue 1, March 2015</b>	Technical Specification for Television White Space Devices
<b>TSAC WG6 Chairman</b>	Mr Yip Yew Seng, ATIS
<b>TSAC WG6 TF1 Chairman</b>	Mr Yip Yew Seng, ATIS Dr Oh Ser Wah, I2R, ASTAR
<b>TSAC WG6 TF1 Editor</b>	Dr Yuen Chau, SUTD
<b>TSAC WG6 TF1 Secretary</b>	Ms Koo Boon Lan, M1

### List of TSAC WG6 TF1 Members

S/N	Organisation	Name
1	Agilent Technologies	Mr Lim Ka Giap
2	AntLab	Mr Aw Peng Soon
3	Huawei	Dr Xu Changqing
4	I2R, ASTAR	Dr Ma YuGang
5	Lock Spectrum	Mr Khoo Teng Lock
6	NEC Asia Pacific	Dr Lua Eng Keong
7	NICT	Dr Zhou MingTuo
8	Power Automation	Mr Kerk See Gim
9	StarHub	Mr Liew Wong Huat
10	ZDW Systems	Mr Charlie Khoo



---

Prof Ko Chi Chung	National University of Singapore Department of Electrical & Computer Engineering
Assoc Prof Tham Chen Khong	National University of Singapore Department of Electrical & Computer Engineering
Mr Chong Siew Loong	Vice President (Network and Systems) Nucleus Connect Pte Ltd
Mr Tiong Onn Seng	Director – Project Netlink Trust Pte Ltd
Mr Aw Peng Soon	Chairman of Digital Media, Wireless Chapter of Singapore Infocomm Technology Federation
Mr Lim Yong Nam	Director (Voice Engineering, Next Gen IP Networks) Singapore Telecommunications Ltd
Mr Lee Yeu Ching	Director (Outside Plant Engineering) Singapore Telecommunications Ltd
Mr Soh Keng Hock	Director (Private IP Engineering) Singapore Telecommunications Ltd
Mr Edmund Quek	Associate Director (Radio Network Performance) Singapore Telecommunications Ltd
Dr Wong Woon Kwong	Director of the Office of Research and Industry Collaborations Singapore University of Technology and Design
–	Standards Division Spring Singapore
Mr Tay Wei Kiang	Assistant Vice President, Business Solutions & Fixed Services StarHub Integrated Network Engineering StarHub Ltd
Mr Liong Hang Chew	Assistant Vice President, Personal Solutions & Integrated Applications StarHub Integrated Network Engineering StarHub Ltd
Ms Woo Yim Leng	Senior Manager (Resource Management & Standards) Infocomm Development Authority of Singapore

## Content

Section	Technical Specification for Television White Space Devices	Page
1	<b>Scope of Specification</b>	1
2	<b>References</b>	1
3	<b>Abbreviations</b>	2
4	<b>General Requirements</b>	3
4.1	Design of WSD	3
4.2	Safety Requirements	3
5	<b>Radio Frequency Interface Requirements</b>	4
5.1	Permissible Channels of Operation and Channel Bandwidth	4
5.2	RF Power and RF Power Spectral Density	5
5.3	Transmitter Unwanted Emissions	5
6	<b>Geo-location Database Interface Requirements</b>	6
6.1	Control and Monitoring Requirements	6
6.1.1	Geo-location Database Identification	6
6.1.2	Transmission in Compliance with Parameters	7
6.1.3	Master WSD Update	8
6.1.4	Client WSD Update	9
6.2	Geo-location Capability	9
6.3	Software, Firmware and User Access Restrictions	10
6.4	Security	10
<b>Annex A</b>	<b>Conformance Testing / Verification Checklist</b>	11

### NOTICE

THE INFOCOMM DEVELOPMENT AUTHORITY OF SINGAPORE (“IDA”) MAKES NO WARRANTY OF ANY KIND WITH REGARD TO THE MATERIAL PROVIDED HEREIN AND EXCLUDES ANY EXPRESS OR IMPLIED WARRANTIES OR CONDITIONS OF NON-INFRINGEMENT, MERCHANTABILITY, SATISFACTORY QUALITY AND FITNESS FOR A PARTICULAR PURPOSE. SUBJECT TO THE MAXIMUM EXTENT PERMITTED UNDER LAW, IDA SHALL NOT BE LIABLE FOR ANY ERRORS AND/OR OMISSIONS CONTAINED HEREIN OR FOR ANY LOSSES OR DAMAGES (INCLUDING ANY LOSS OF PROFITS, BUSINESS, GOODWILL OR REPUTATION, AND/OR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES) IN CONNECTION WITH THE USE OF THIS MATERIAL.

IDA DRAWS ATTENTION TO THE POSSIBILITY THAT THE PRACTICE OR IMPLEMENTATION OF THIS STANDARD MAY INVOLVE THE USE OF INTELLECTUAL PROPERTY RIGHTS AND TAKES NO POSITION CONCERNING THE EXISTENCE, VALIDITY AND/OR APPLICABILITY OF ANY SUCH INTELLECTUAL PROPERTY RIGHTS, WHETHER ASSERTED BY TSAC MEMBERS OR ANY THIRD PARTY.

AS OF THE DATE OF APPROVAL OF THIS STANDARD, IDA HAS NOT RECEIVED WRITTEN NOTICE OF ANY PATENT RIGHTS WHICH MAY BE RELEVANT IN RELATION TO THE IMPLEMENTATION OF THIS STANDARD. HOWEVER, IMPLEMENTERS ARE CAUTIONED THAT THIS MAY NOT REPRESENT THE LATEST INFORMATION AND ARE THEREFORE STRONGLY URGED TO CHECK WITH THE RELEVANT DATABASE IN ITU, ISO, IEC OR THE RELATED STANDARDS DEVELOPMENT ORGANISATION FOR INFORMATION OF PATENT RIGHTS. IMPLEMENTERS ARE ADVISED TO OBTAIN THEIR OWN LEGAL AND/OR TECHNICAL ADVICE IN RELATION TO THE IMPLEMENTATION OF THE STANDARD IF REQUIRED.

## 1 Scope of Specification

- 1.1 This Specification defines the technical requirements of Television (“TV”) Band or White Space Devices (“WSD”) that may be permitted to operate on any available TV channels of the broadcast TV frequency bands as shown in Table 1.
- 1.2 This Specification is applicable to the following types of radio equipment:
  - a. A fixed WSD which may be a master WSD, capable of communicating directly with a Geo-location Database, and operating as a network, transmitting to and receiving from one or more fixed WSDs and/or personal/portable WSDs. A fixed WSD is geo-located and operates from a fixed location.
  - b. A personal/portable mode II WSD, which may also be a master WSD, capable of communicating directly with a Geo-location Database, and operating as a network, transmitting to and receiving from one or more fixed WSDs or personal/portable WSDs. A mode II WSD operates with a geo-location capability.
  - c. A personal/portable mode I WSD is a client WSD, capable of only communicating with other WSDs under the control of a serving master WSD. A mode I WSD does not operate with a geo-location capability.

## 2 References

In establishing the technical requirements of this Specification, reference has been made to the following documents:

- [1] ETSI EN 301 489-1 V1.9.2 (2011-9), Electromagnetic compatibility and Radio spectrum Matters (ERM); ElectroMagnetic Compatibility (EMC) standard for radio equipment and services; Part 1: Common technical requirements
- [2] IEC CISPR 22 (2008), Information Technology Equipment - Radio disturbance characteristics – Limits and methods of measurement
- [3] IEC 60950-1(2005-12), International Electrotechnical Commission – Safety of Information Technology Equipment
- [4] ETSI EN 301 598 V1.0.9 (2014-02), White Space Devices (WSD); Wireless Access Systems operating in the 470 MHz to 790 MHz TV broadcast band; Harmonized EN covering the essential requirements of article 3.2 of the R&TTE Directive
- [5] FCC Title 47 CFR Ch. I (10–1–10 Edition), Part 15 - Radio Frequency Devices  
Subpart C – Intentional Radiators, §15.209 Radiated emission limits  
Subpart H – Television Band Devices
- [6] 416721 D01 White Space Test Procedures v02, FCC OET Lab Div (6/25/2012), Certification Test Procedures for TV Band (White Space) Devices Authorized under Subpart H of the Part 15 Rules

### 3 Abbreviations

ACLR	Adjacent Channel Leakage Ratio
C	Conditional
CISPR	International Special Committee on Radio Interference
CR	Compliance Requirement
EIRP	Equivalent Isotropically Radiated Power
EMC	Electromagnetic Compatibility
EMF	Electromagnetic Field
ETSI	European Telecommunications Standards Institute
FCC	Federal Communications Commission
ICNIRP	International Commission on Non-Ionising Radiation Protection
IEC	International Electrotechnical Commission
M	Mandatory
OUI	IEEE Organisationally Unique Identifier
PSD	Power Spectral Density
RF	Radio Frequency
TV	Television
TVWS	Television White Space
UHF	Ultra High Frequency
UUID	IETF Universally Unique Identifier
VHF	Very High Frequency
WSD	White Space Devices

## **4 General Requirements**

### **4.1 Design of WSD**

The WSD shall be designed to meet the following requirements:

- a. The WSD shall not cause harmful interference to radio-communication services operating in allocated frequency bands, and cannot claim protection from these radio-communication services;
- b. The personal/portable Mode I or mode II WSD shall be fixed with an integral or a dedicated antenna that has been assessed with the WSD for compliance with the requirements of this Specification;
- c. The fixed WSD may have an external antenna, with the antenna connector;
- d. The WSD shall not be constructed with any external or readily accessible control which permits the adjustment of its operation in a manner that is inconsistent with this Specification; and
- e. The WSD shall be marked with the supplier/manufacture's name or identification mark, and the supplier/manufacture's model or type reference. The markings shall be legible, indelible and readily visible.

### **4.2 Safety Requirements**

4.2.1 Where appropriate, the WSD shall be tested according to measurement methods and limits for:

- a. Electromagnetic Compatibility ("EMC") emissions from the direct DC power or AC mains power input/output ports defined in ETSI EN 301 489-1 [1] or IEC CISPR 22 [2]; and
- b. Electrical safety defined in the IEC 60950-1 [3].

4.2.2 Where appropriate, the WSD shall comply with the International Commission on Non-Ionising Radiation Protection ("ICNIRP") guidelines for limiting exposure to time-varying electromagnetic field ("EMF") in the frequency range up to 300 GHz.

4.2.3 It should be noted that compliance with any radiation safety standard does not by itself confer immunity from legal obligations and requirements imposed by national health or safety authorities.



## 5 Radio Frequency Interface Requirements

### 5.1 Permissible Channels of Operation and Channel Bandwidth

- 5.1.1 A nominal channel is defined as one (or more contiguous) TV channel(s) specified by an authorised Geo-location Database for its permitted transmissions. The nominal channel bandwidth shall be 7 MHz (or multiple of 7 MHz) for WSD operating in the Very High Frequency (“VHF”) band; or 8 MHz (or multiple of 8 MHz) for WSD operating in the Ultra High Frequency (“UHF”) band.
- 5.1.2 Fixed and mode II WSD shall operate only on available TV channels as identified in Table 1, and as specified by an authorised Geo-location Database.
- 5.1.3 Mode I WSD shall operate only on available TV channels as identified in Table 1, provided by a fixed or mode II WSD.
- 5.1.4 Available TV channels and frequencies for Television White Space (“TVWS”) operations are as shown in Table 1.

TV Band	Frequencies / Channel(s)	Channel Bandwidth	Total Bandwidth / No. of Channels
VHF III	181 – 188 MHz (Channel 6)	7 MHz	21 MHz (3 channels)
	209 – 223 MHz (Channel 10 and 11)		
UHF V	614 – 622 MHz (Channel 39)	8 MHz	168 MHz (21 channels)
	630 – 710 MHz (Channel 41 to 50)		
	718 – 742 MHz (Channel 52 to 54)		
	750 – 774 MHz (Channel 56 to 58)		
	790 – 806 MHz (Channel 61 and 62)		
<p>Note 1: When Analogue Switched Off (“ASO”) occurs (which will likely take place by 2020), and the 700 MHz band (694 – 806 MHz) has been harmonized and allocated for the International Mobile Telecommunications (“IMT”) services, 14 channels (Channel 49 to 62) will be removed from the TVWS usage. Industry will be duly notified.</p> <p>Note 2: Channels 25 and 26 shall be blocked from TVWS operations by the Geo-location Database until further field tests have been conducted on adjacent channel interference.</p> <p>Note 3: Channel 47 shall also be blocked from TVWS operations by the Geo-location Database, as Channels 25 and 47 will be utilised for safe harbour operations of wireless microphones, operating in permitted frequency bands defined in the IDA Technical Specification for Short Range Devices (“IDA TS SRD”).</p>			

**Table 1: TV Channels for TVWS Operations**

## 5.2 RF Power and RF Power Spectral Density

- 5.2.1 The Radio Frequency (“RF”) power within the nominal channel shall not exceed the level as determined by an authorised Geo-location Database; or as indicated by a master WSD (which is a fixed or mode II WSD) to the client WSD (mode I WSD) for operations in that channel. The equivalent isotropically radiated power (“EIRP”) over the 7 MHz channel bandwidth or 8 MHz channel bandwidth on which the type of WSD is permitted to operate, shall be within the limits as specified in Table 2.

Transmission Power (EIRP) over a TV channel	Fixed WSD	Mode II WSD	Mode I WSD
	4 W (36 dBm)	100 mW (20 dBm)	100 mW (20 dBm)
Note: EIRP is the product of the power supplied to the antenna and the antenna gain in a given direction relative to an isotropic antenna.			

**Table 2: Power Limits for WSD**

- 5.2.2 The WSD shall incorporate transmit power control feature to limit the transmission power to the minimum possible for successful communication.
- 5.2.3 The RF power spectral density from the WSD shall not exceed the following values when measured in any 100 kHz bandwidth within the TV channel specified by an authorised Geo-location Database or provided by a master WSD:
- For fixed WSD, the transmission power shall not exceed 17.5 dBm EIRP (PSD in 100 kHz) transmitting in 7 MHz channel bandwidth; or 17 dBm EIRP (PSD in 100 kHz) operating in 8 MHz channel bandwidth.
  - For mode I or mode II WSD, the transmission power shall not exceed 1.55 dBm EIRP (PSD in 100 kHz) transmitting in 7 MHz channel bandwidth; or 0.97 dBm EIRP (PSD in 100 kHz) transmitting in 8 MHz channel bandwidth.

## 5.3 Transmitter Unwanted Emissions

- 5.3.1 Emissions from the personal/portable mode I or II WSD shall not exceed – 56.8 dBm EIRP in a resolution bandwidth of 100 kHz, measured in the local broadcast TV channels that are adjacent to the channel in which the WSD is operating.
- 5.3.2 Emission limits for the fixed WSD shall not exceed – 42.8 dBm conducted power in a resolution bandwidth of 100 kHz, measured in the local broadcast TV channels that are adjacent to the channel in which the WSD is operating.
- 5.3.3 For WSDs that conform to Device Emission Classes given in Table 2, § 4.2.4.2 of EN 301 598 [4], unwanted emissions from WSD outside the nominal channels (out-of-block) within the broadcast TV frequency bands, shall be comply with the following limits:

Out-of-block EIRP spectral density of a WSD,

$$P_{\text{OOB}} \text{ (dBm / 100 kHz)} \leq (P_{\text{IB}} - \text{ACLR}),$$

where  $P_{\text{IB}}$  is the measured in-block EIRP spectral density over 8 MHz, and ACLR is the adjacent channel leakage ratio (dB), outlined in Table 2, § 4.2.4.2 of EN 301 598 [4] for different Device Emission Classes.

- 5.3.4 At frequencies beyond the local broadcast TV channels, but are adjacent to the channel in which the WSD is operating, the radiated emissions from the WSD shall meet the requirements of FCC CFR 47 Part 15 § 15.209 [5]; or § 4.2.4.1 of EN 301 598 [4].

## **6 Geo-location Database Interface Requirements**

### **6.1 Control and Monitoring Requirements**

The control and monitoring requirements ensure that:

- a. The WSD shall not transmit in the absence of communications with an authorised Geo-location Database, or a master WSD.
- b. The WSD shall transmit in accordance with the parameters provided by an authorised Geo-location Database.
- c. The WSD shall not obtain parameters from an unauthorised Geo-location Database.

Note: The protocol used for data transfer between client WSDs, master WSDs and Geo-location Databases are outside the scope of this Specification.

#### 6.1.1 Geo-location Database Identification

- 6.1.1.1 At start up and before initiating any transmissions in the TV frequency bands, the master WSD (mode II or fixed WSD) shall ensure that the Geo-location Database which it queries is authorised by IDA. Development and availability of the Geo-location Database will be updated.

Note: A fixed WSD equipped with spectrum sensing capability may also use spectrum sensing as a complementary method, as long as no interference is caused to users of radio-communication services.

- 6.1.1.2 The master WSD shall not request operational parameters from a Geo-location Database that is not approved by IDA.

6.1.2 Transmitting in Compliance with Parameters

Parameter sets are outlined in Table 3 <sup>(Note 1)</sup>.

Parameter Set	Information Element	Description
<u>Device Parameters</u> <small>(Note 2)</small>  For mode I WSD to communicate with mode II / fixed WSD; and for mode II / fixed WSD to communicate with Geo-location Database	Antenna location	Latitude and longitude coordinates, and altitude <sup>(Note 3)</sup>
	Antenna location accuracy	Accuracy of $\pm 50$ metres determined by internal geo-location capability or manual entry of geographical coordinates
	Device type	Fixed WSD, Personal/Portable Mode I or Mode II WSD
	Device Emission Class	Class number of which the WSD complies with as outlined in Table 2, § 4.2.4.2 of EN 301 598 [4]
	Unique device identifier - Manufacturer identifier - Model identifier - Serial number	IEEE Organisationally Unique Identifier ("OUI"), IETF Universally Unique Identifier ("UUID") (RFC 4122) or FCC ID
<u>Operational Parameters</u> <small>(Note 4)</small>  Use by any WSD to configure its transmissions within the TV channels approved for TVWS operations.  All operational parameters are generated by the Geo-location Database and communicated to the mode II / fixed WSD.	List of TV channel edge frequency pairs	This is the list of frequency blocks where the WSD is allowed to transmit.
	Max RF EIRP spectral density for each TV channel edge frequency pair	Power (dBm / 100 kHz) over the frequency band
	Max RF EIRP for each TV channel edge frequency pair	Power (dBm) over the frequency band
	Max total bandwidth	Max total bandwidth (in Hz), may or may not be contiguous
	Time validity start ( $T_{VALSTART}$ )	Time when operational parameters start being valid.
	Time validity end ( $T_{VALEND}$ )	Time when operational parameters stop being valid. For client WSD (mode I WSD), the serving master WSD may indicate a permitted duration of operation, specified as $T_{DUR}$ .
	Location validity ( $L_{VAL}$ )	$L_{VAL}$ is 100 metres from the original position, outside of which operational parameters are not valid.
Update timer ( $T_{UPDATE}$ )	This indicates how often the master WSD will check with the Geo-location Database that operational parameters are still valid. $T_{UPDATE}$ is 6 hours, and is configurable.	
<p>Note 1: Specific protocol implementations may use different names for the parameter sets or for individual information elements.</p> <p>Note 2: If any of the device parameters cannot be reported to the Geo-location Database or the master WSD, the WSD shall indicate that the parameter is not available.</p> <p>Note 3: Height of antenna (or altitude of antenna location) is defined as the height above ground, which will enable a Geo-location Database to general operational parameters based on the altitude of the WSD.</p> <p>Note 4: The algorithms to calculate operational parameters and the assumptions for these calculations are outside the scope of this Specification.</p>		

**Table 3: Device and Operational Parameters**

- 6.1.2.1 The WSD shall not start transmissions in the TV frequency bands unless it has received operational parameters from a Geo-location Database; or from a master WSD.
- 6.1.2.2 The WSD shall, at any point in time, only transmit in accordance with the operational parameters that it has received from a Geo-location Database; or from a master WSD.
- Note: Communication between two client WSDs is permitted, provided that each is operating in accordance with the operational parameters given by its serving master WSD.
- 6.1.2.3 The fixed WSD which requires operational parameters from the Geo-location database shall first accurately report its own device parameters to the Geo-location database to obtain a successful registration.
- 6.1.2.4 The Geo-location database will indicate a failed registration if any of the following parameter or information provided is invalid:
- a. Unique device identifier
  - b. Device geographic coordinates (latitude and longitude)
  - c. Height of antenna (altitude)
  - d. Licensee contact information
- 6.1.2.5 A fixed WSD may confirm its registration through a registered fixed WSD on a TV channel indicated as available to that registered fixed WSD.
- 6.1.2.6 The mode II WSD which requires operational parameters from the Geo-location database shall accurately report its own device parameters to the Geo-location database. The mode II WSD may obtain operational parameters for multiple locations in the vicinity of its current location, and use such information to define a geographical area in which it can operate with the same operational parameters.
- 6.1.2.7 A master WSD (mode II or fixed WSD) shall report to the Geo-location database its own unique device identifier together with the unique device identifiers of the client WSDs (mode I WSDs) that transmit using a subset of the operational parameters obtained from the Geo-location database.
- 6.1.2.8 The mode I WSD which intends to use the operational parameters provided by a master WSD, shall accurately report its unique device identifier to the serving master WSD. Once the mode I WSD (client WSD) receives contact verification signal from the serving master WSD, it can start transmission using the operational parameters received from the master WSD.
- 6.1.3 Master WSD Update
- 6.1.3.1 The master WSD (mode II or fixed WSD) update is a process in which the Geo-location Database informs the master WSD that its operational parameters, and those of the client WSDs attached to it, are still valid or are no longer valid. The update can be initiated by either the master WSD or the Geo-location Database. The master WSD shall support this WSD update function.
- 6.1.3.2 The master WSD shall cease transmission, and instruct the client WSDs attached to it to cease transmission, if it receives update from the Geo-location Database that the parameters are no longer valid.
- 6.1.3.3 A master WSD shall cease transmission, and instruct the client WSDs attached to it to cease transmission, if it fails to connect with the Geo-location Database for a period which exceeds  $T_{UPDATE}$ .  $T_{UPDATE}$  is one of the operational parameters defined in Table 3.
- 6.1.3.4 A master WSD shall support an update every  $T_{UPDATE}$ .
- 6.1.3.5 A mode II WSD using operational parameters for multiple locations shall initiate update with the Geo-location Database when it moves beyond the boundary of the area where the operational

---

parameters are valid. Regardless, such mode II WSD shall verify the validity of the operational parameters with the Geo-location Database on a daily basis.

- 6.1.3.6 A WSD is allowed to enter a sleep mode, i.e. inactive but not powered down. A master WSD which is in sleep mode does not need to be reachable by the Geo-location Database, nor need to contact the Geo-location Database, while it remains in sleep mode.
- 6.1.3.7 A master WSD which has been in sleep mode for longer than  $T_{UPDATE}$  shall not restart transmissions according to the operational parameters obtained before going into sleep mode. It shall only restart transmissions after its operational parameters have been updated by the Geo-location Database.
- 6.1.4 Client WSD update
- 6.1.4.1 The client WSD (mode I WSD) update is the process by which a master WSD informs a client WSD that its operational parameters are still valid or are no longer valid. The update can be initiated by either the client WSD or the master WSD. The client WSD shall support this WSD update function.
- 6.1.4.2 A client WSD shall cease transmission when the master WSD informs the client WSD that its operational parameters are no longer valid.
- 6.1.4.3 A client WSD shall cease transmission if it fails to receive an update (or a contact verification signal from), or fails to re-establish the operational parameters with its serving master WSD every 60 seconds.
- 6.1.4.4 A WSD is allowed to enter a sleep mode, i.e. inactive but not powered down. A client WSD which is in sleep mode does not need to be reachable by the master WSD, nor need to contact the master WSD while it remains in sleep mode.
- 6.1.4.5 A client WSD that has been in sleep mode for more than 60 seconds shall not restart transmissions until it has re-confirmed its operational parameters with the serving master WSD.

## 6.2 Geo-location Capability

- 6.2.1 Geo-location capability is the capability of a WSD to determine and report its latitude and longitude (i.e. horizontal geo-location capability) and altitude (i.e. vertical geo-location) coordinates of its antenna. A fixed WSD may have a horizon geo-location capability, a mode II WSD shall have a horizon geo-location capability, and a mode I WSD does not require a horizon geo-location capability. A WSD with a horizon geo-location capability may also have a vertical geo-location.
- 6.2.2 A WSD which has geo-location capability and is able to determine its location:
- WSD shall report its geo-location coordinates of its antenna(s), as part of its device parameters; and
  - WSD shall report its geo-location accuracy (in metres), as part of its device parameters.
- 6.2.3 At the time of installation and first activation from a power-off condition, the fixed WSD shall determine its geo-location and accuracy, and store this information in the WSD, either by means of its incorporated geo-location capability or manual entry. If the fixed WSD is moved to another location, registration with the Geo-location Database based on its new geo-location and accuracy shall be required.
- 6.2.4 A client WSD (mode I WSD) does not require a geo-location capability as it is relying on its serving master WSD (mode II or fixed WSD) to determine its operational parameters.

- 6.2.5 A mode II WSD whose location is more than  $L_{VALUE}$  away from the location reported to the Geo-location Database shall not transmit according to the operational parameters determined for that reported location.

Note:  $L_{VALUE}$  is part of the set of operational parameters.

- 6.2.6 A mode II WSD which has previously reported a location to the Geo-location Database, but it is no longer able to determine its location shall stop transmitting in accordance with the existing operational parameters.

### **6.3 Software, Firmware and User Access Restrictions**

- 6.3.1 Software, firmware and user access restrictions are those measures which are intended to prevent changes, which could adversely affect the compliance of the WSD with the requirements defined in this Specification.
- 6.3.2 The configuration of the WSD (or equipment) shall not be made dependent of the correct selection by the user of the appropriate country operation, or any other setting to be input by the end-user.
- 6.3.3 The WSD shall not allow the end-user to have access to any hardware or software settings that can affect:
- a. Geo-location Database identification;
  - b. Exchange of the parameters outlined in Table 3, communicated between a WSD and a Geo-location Database or a master WSD; and
  - c. Compliance with the requirements defined in this Specification.
- 6.3.4 Manufacturers who provide their software or firmware as open source code shall prevent modified software from having any impact on the compliance of the WSD with the requirements in this Specification.

### **6.4 Security**

- 6.4.1 Security is defined as measures to support the concepts of Authentication and Integrity.
- 6.4.2 Authentication
- a. A master WSD shall authenticate the Geo-location Database using a widely accepted Internet authentication mechanism.
  - b. A master WSD shall not communicate its device parameters or the device parameters of a client WSD to a Geo-location Database that has not been authenticated.
  - c. A master WSD shall not use operational parameters obtained from a Geo-location Database that has not been authenticated.
  - d. A master WSD shall not provide operational parameters to a client WSD from a Geo-location Database that has not been authenticated.
- 6.4.3 Integrity
- a. A master WSD shall communicate with the Geo-location Database using a protocol that includes functionality to avoid tampering with the exchange of parameters in transit.
  - b. A master WSD and a client WSD shall communicate using a protocol that includes functionality to avoid corruption of the parameters in transit.

## Annex A

### Conformance Testing / Verification Checklist

This Checklist is intended for facilitating Supplier's Declaration of Conformity to the technical requirements defined in the IDA Technical Specification for Television White Space Devices ("IDA TS WSD").

**Please note:**

"**CR**" indicates that the technical requirement set out in a particular section or sub-section ("§") of the IDA TS WSD is a **Compliance Requirement**.

"**M**" means that it shall be **Mandatory** for the WSD to comply with the technical requirement set out in the IDA TS WSD § cited in this Checklist (Table given below).

"**C**" means that compliance with the technical requirement set out in the IDA TS WSD § cited in this Checklist is **Conditional**. In this case, the need to comply is contingent on the type of WSD as indicated in the remarks column.

IDA TS WSD §	Parameter	Reference [n] given in § 2 of TS WSD	CR	Yes /No	Remarks
1.2	Type of device: Fixed; personal/portable mode I; or personal/portable mode II WSD	[4] § 4.2.1.1 or § 4.2.1.2; or [5] § 15.703(c), § 15.703(e) or § 15.703(f)	M		State what is the type of WSD.
4.1	Design of WSD	[4] § 4.2.1 and § 5.1.2; or [5] § 15.709(b), and [6] Part 1: 2(d)	M		
4.2	Safety requirements		M		
5.1	Permissible channels and channel bandwidth	[6] Part 1: 2(b)i, [5] § 15.711(c), and [6] Part 2: 2(j)	M		Verify that the WSD cannot be tuned to operate on unauthorised TV channels. Confirm WSD channel availability.
5.2.1, Table 1	Transmission power over a TV channel	[4] § 4.2.3.2, § 5.3.2 and § 5.3.3; or [6] Part 1: 2(c)i or 2(c)ii	M		
5.2.2	Transmit power control	[5] § 15.709(a)(3)	M		Provide a description of this mechanism incorporated in the WSD.
5.2.3	RF power spectral density	[4] § 4.2.3.2, § 5.3.2 and § 5.3.3; or [6] Part 1: 2(c)i or 2(c)ii Radiated measurement procedure for fixed WSD may utilise the ANSI C63.4-2009 for guidance.	M		When conducted measurement is used for fixed WSD with external antenna, the sum of the total conducted power within the TV channel bandwidth and the antenna gain shall not exceed 4W EIRP.
5.3.1	Out-of-band emissions from personal/portable mode I or II WSD measured in local TV channels adjacent to the WSD operating channel	[6] Part 1: 2(e) and (e)ii	C		Applicable to WSDs defined in § 15.703(c) and § 15.709(c)(i)
5.3.2	Out-of-band emissions from fixed WSD measured in local TV channels adjacent to WSD operating channel	[6] Part 1: 2(e) and (e)ii	C		Applicable to WSDs defined in § 15.703(e), (f) and § 15.709(c)(iv)



IDA TS WSD §	Parameter	Reference [n] given in § 2 of TS WSD	CR	Yes /No	Remarks
5.3.3	Out-of-block EIRP spectral density	[4] § 4.2.4.2 and § 5.3.5	C		Applicable to WSDs that conform to Device Emission Classes given in [1] Table 2, § 4.2.4.2
5.3.4	Emissions at frequencies beyond local TV channels, but adjacent to WSD operating channel	[6] Part 1: 2(e)iii; or [4] § 4.2.4.1 and § 5.3.4	M		
6.1	Control and monitoring requirements	[4] § 5.3.11 or [5] § 15.709(a)(6)	M		
6.1.1	Geo-location database identification	[4] § 5.3.11.1 or [5] § 15.709(a)(6)	M		
6.1.2	Transmitting in compliance with parameters	[4] § 5.3.11.2 or [5] § 15.713(f)(3), and (g); [5] § 15.711(b)(3)(iv); [5] § 15.707(a); and [6] Part 2: 2(a) to 2(d)	M		
6.1.3	Master WSD update	[4] § 5.3.11.2 or [5] § 15.711(b)(2) [5] § 15.711(b)(3)(i), (ii), and (iii); and [6] Part 2: 2(e) to (f)	M		[5] § 15.711(b)(3)(i)(ii) and [6] Part 2: 2(h) 48 Hour Channel Scheduling – Applicable?
6.1.4	Client WSD update	[4] § 5.3.11.2 or [5] § 15.711(b)(3)(iv), § 15.711 (g)	M		
6.2	Geo-location capability	[4] § 5.3.12 or [5] § 15.711(b)(1) and (2)	C		Requirement is optional for fixed WSD; mandatory for Mode II WSD; and need not apply to Mode I WSD.
6.3	Software, firmware and user access restriction		M		Application shall include a high level description of the measures taken.
6.4	Security	[5] § 15.711(b)(3)(vi), (f)	M		Application shall include a high level description of the technologies and measure incorporated in the WSD to comply with the security requirements of this section.